

ONTEC PROSAT POLYNIT HEATSEAL 70/30 IPA & DI WATER

Page: 1

Compilation date: 15/01/2016

Revision date: 13/06/2017

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CONTEC PROSAT POLYNIT HEATSEAL 70/30 IPA & DI WATER

Product code: PSPS0047 PS-HS9-7030

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: Contec Inc.

525 Locust Grove

Spartanburg

South Carolina

29303

USA

Tel: +33 (0) 2 97 43 76 98

Email: sds@contecinc.com

1.4. Emergency telephone number

Emergency tel: +1 703 527 3887 (24 hours)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; STOT SE 3: H335

Most important adverse effects: Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or

dizziness. May cause respiratory irritation.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H335: May cause respiratory irritation.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





CONTEC PROSAT POLYNIT HEATSEAL 70/30 IPA & DI WATER

Page: 2

Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P243: Take precautionary measures against static discharge.

P370+378: In case of fire: Use dry chemical, carbon dioxide to extinguish.

P280: Wear protective gloves, protective clothing and eye protection.

P261: Avoid breathing mist/vapours/spray.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with.

P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P312: Call a if you feel unwell.

2.3. Other hazards

Other hazards: Highly flammable. Irritating to eyes. Irritating to respiratory system. May cause sensitisation

by skin contact. May cause sensitisation by inhalation.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Non-classified ingredients:

PROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	50-70%
			STOT SE 3: H336	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the

affected skin with running water for 10 minutes or longer if substance is still on skin. Get

medical attention if irritation develops or persists.

Eye contact: Bathe the eye with running water for 15 minutes. Remove contact lenses, if present and easy

to do so. If eye irritation persists, get medical advice/attention.

Ingestion: Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

CONTEC PROSAT POLYNIT HEATSEAL 70/30 IPA & DI WATER

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Carbon dioxide. Dry chemical powder. Water fog. Water spray. Do not

use water.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Evacuate the area immediately. Mark out the contaminated area with signs and prevent

access to unauthorised personnel. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may

produce sparks. Transfer to a closable, labelled salvage container for disposal by an

appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the

air. Earth any equipment used in handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container

tightly closed. Keep away from direct sunlight. Prevent the build up of electrostatic charge in the immediate area. Avoid incompatible materials and conditions - see section 10 of SDS. Do

not freeze. Store below 40°C.

Suitable packaging: Must only be kept in original packaging.

CONTEC PROSAT POLYNIT HEATSEAL 70/30 IPA & DI WATER

Page: 4

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Use an EN149 approved respirator if exposure limits are exceeded or if irritation or other

symptoms are experienced.

Hand protection: Neoprene gloves. Rubber gloves. PVC gloves. Nitrile gloves.

Eye protection: Tightly fitting safety goggles. Face-shield. Ensure eye bath is to hand.

Skin protection: Ensure safety shower is to hand.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid presaturated wipes.

Odour: Alcoholic

Boiling point/range°C: 82-89 Melting point/range°C: No data available.

Flammability limits %: lower: 2 upper: 12

Flash point°C: 20.5 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: 399 Vapour pressure: 43.0hpa @ 20°C

Relative density: No data available. **pH:** No data available.

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

CONTEC PROSAT POLYNIT HEATSEAL 70/30 IPA & DI WATER

Page: 5

10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong oxidising agents. Halogens.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
DERMAL	RBT	LD50	12800	mg/kg
ORAL	MUS	LD50	3600	mg/kg
ORAL	RAT	LD50	5045	mg/kg

Hazardous ingredients:

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
DAPHNIA	96H LC50	10000000	μg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

CONTEC PROSAT POLYNIT HEATSEAL 70/30 IPA & DI WATER

Page: 6

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3175

14.2. UN proper shipping name

Shipping name: SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL).

(PROPAN-2-OL; WATER)

14.3. Transport hazard class(es)

Transport class: 4.1

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 2

Section 15: Regulatory information

CONTEC PROSAT POLYNIT HEATSEAL 70/30 IPA & DI WATER

Page: 7

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation. H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.