

Page: 1

Compilation date: 01/12/2015

Revision date: 13/06/2017

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CONTEC PROSAT STERILE MBPP WITH 70% DENATURED ETHANOL

Product code: PS-911EB/ETOH

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Contec Inc.

525 Locust Grove

Spartanburg

South Carolina

29303

USA

Tel: +33 (0) 2 97 43 76 98

Email: sds@contecinc.com

1.4. Emergency telephone number

Emergency tel: +1 703 527 3887 (24 hours)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336

Most important adverse effects: Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or

dizziness.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

CONTEC PROSAT STERILE MBPP WITH 70% DENATURED ETHANOL

Page: 2

No smoking.

P370+378: In case of fire: Use dry chemical/carbon dioxide to extinguish.

P260: Do not breathe vapours.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with.

P312: Call a if you feel unwell.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

P411: Store at temperatures not exceeding 40 °C.

P501: Dispose of contents/container to hazardous waste.

2.3. Other hazards

Other hazards: Irritating to eyes. Irritating to respiratory system. Irritating to skin.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	50-70%
PROPAN-2-OL				

.....

200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	1-10%
			STOT SE 3: H336	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the

affected skin with running water for 10 minutes or longer if substance is still on skin. Consult

a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Remove contact lenses, if present and easy

to do so. If eye irritation persists, get medical advice/attention.

Ingestion: Do not induce vomiting. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air

in case of accidental inhalation of vapours. Consult a doctor.

[cont...]

CONTEC PROSAT STERILE MBPP WITH 70% DENATURED ETHANOL

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol resistant foam. Water spray. Water fog.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Evacuate the area immediately. Eliminate all sources of ignition. Mark out the contaminated

area with signs and prevent access to unauthorised personnel. Do not attempt to take action

without suitable protective clothing - see section 8 of SDS.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may

produce sparks. Transfer to a closable, labelled salvage container for disposal by an

appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the

air. Earth any equipment used in handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container

tightly closed. Keep away from direct sunlight. Prevent the build up of electrostatic charge in the immediate area. Avoid incompatible materials and conditions - see section 10 of SDS. Do

not freeze. Store below 40°C.

Suitable packaging: Must only be kept in original packaging.

CONTEC PROSAT STERILE MBPP WITH 70% DENATURED ETHANOL

Page: 4

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1000ppm	-	-	-

Hazardous ingredients:

ETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1920 mg/m3	-	-	-

PROPAN-2-OL

	UK	999 mg/m3	1250 mg/m3	-	
--	----	-----------	------------	---	--

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Use an EN149 approved respirator if exposure limits are exceeded or if irritation or other

symptoms are experienced.

Hand protection: PVC gloves. Nitrile gloves. Neoprene gloves. Rubber gloves.

Eye protection: Tightly fitting safety goggles. Face-shield. Ensure eye bath is to hand.

Skin protection: Protective clothing. Ensure safety shower is to hand.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid presaturated wipes.

Colour: Colourless
Odour: Alcoholic

Boiling point/range°C: 78 Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 22 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: 399 **Vapour pressure:** No data available.

Relative density: No data available. **pH:** No data available.

VOC g/I: 100%

CONTEC PROSAT STERILE MBPP WITH 70% DENATURED ETHANOL

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: No data available.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong oxidising agents. Halogens.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

CONTEC PROSAT STERILE MBPP WITH 70% DENATURED ETHANOL

Page: 6

Symptoms / routes of exposure

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3175

14.2. UN proper shipping name

Shipping name: SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.

(ETHANOL; PROPAN-2-OL)

14.3. Transport hazard class(es)

Transport class: 4.1

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

CONTEC PROSAT STERILE MBPP WITH 70% DENATURED ETHANOL

Page: 7

14.6. Special precautions for user

Tunnel code: E
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.