



# Quiltec® I Polyester Flat Mop Head

Two-ply quilted polyester flat mop head with synthetic core

## Description

Quiltec I Polyester Mop Heads have been specifically designed for use with Contec's Mop Saturation System 2787. With high absorbency the mops are suitable for single use saturation, giving a surface coverage up to approximately 20 sq. m. The mop head system is designed for hands-free fitting to the mop head frame.

The mop heads are compatible with the QuickTask hinged mop frame 2749.

The Quiltec I Polyester Mop Heads are constructed from a two-ply quilted 100% polyester on the outer face with a synthetic fiberfill core. This provides a highly sorbent mop head which is suitable for the application of disinfectants and removal of light soil, residues and biofilms. Designed for single use, the mop heads are compatible with a wide range of chemicals and disinfectants.

The MHQT0150 is provided sterile by gamma irradiation at no less than 25 kGy.

## Technical Data

Mop head component materials (cleaning surface first)	Two-ply 100% knitted polyester / synthetic fiberfill core
Construction	Multi-layer sewn lamination

Attribute; (units)	Value	Test Method
Mop weight, dry; (g/mop)	57	CTM 004-03
Sorbency in water (mL/mop)	345	CTM 004-03
Non-volatile residue, NVR		IEST-RP-CC004.3, Sec. 7.1.2
In deionized water; (g/m <sup>2</sup> )	0.005	
In isopropanol; (g/m <sup>2</sup> )	0.010	
Particles, readily releasable		IEST-RP-CC004.2, Sec. 5.2
P ≥ 0.5µm; (x10 <sup>6</sup> /m <sup>2</sup> )	33.88	
Fibers > 100µm; (x10 <sup>3</sup> /m <sup>2</sup> )	3.60	IEST-RP-CC004.2, Sec. 5.2

Part Number	Description	EA/OB1	OB1/OB2	OB2/CS	EA/CS
MHQT0100	Quiltec I Polyester Mop Head, 39 x 13cm nominal	5	1	8	40
MHQT0150	Quiltec I Polyester Mop Head, 39 x 13cm nominal, Sterile	5	1	8	40

Key: EA = Each, OB1 = Outer Bag 1, OB2 = Outer Bag 2, CS = Case

### Notes:

- 1) The information presented here is applicable to the part numbers shown above as well as to any product containing the same materials and produced under the same conditions, regardless of product size or packaging configuration. Please contact a Contec sales representative for more details.
- 2) Data shown are typical values and should not be used as product specifications.
- 3) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- 4) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Revision date: 5/24/17



Copyright © 2017 Contec, Inc. All rights reserved.

**North America**  
P.O. Box 530  
Spartanburg, SC 29304 USA  
Phone: +1-864-503-8333  
www.contecinc.com

**Europe**  
Zl du Prat – RP 3707  
56037 VANNES Cedex  
FRANCE  
+33 297 437 690

**China**  
No.17 Longyun Road  
Suzhou 215024  
CHINA  
+ 86-512-6274 4050