



SATWipes™ SAT-C3-694 Wipes

Saturated nonwoven polyester wipes in center-pull dispenser

Description

The SAT-C3-694 consists of a roll of (100) 6" x 9" saturated wipes that are dispensed through a convenient center-pull canister. The wipes consist of 100% nonwoven polyester fabric that is hydraulically entangled creating a soft, durable, and clean wipe that allows for consistent solvent application and use. Saturation level of 600 mL with 6% alcohol and 94% deionized water provides a safe and mild cleaning solution. Reduce solvent handling and use by up to 35%. Refill rolls are available so the pop-up dispenser canister may be reused, eliminating the need for solvent bottles.

Technical Data

Wipe material	100% polyester	
Wipe construction	Hydroentangled nonwoven	
Solution of saturation; (blend ratio and constituents)	6% isopropanol/ 94% deionized water	
Attribute; (units)	Value **	Test Method
Basis weight; (g/m ²)	69	
Non-volatile residue, NVR		IEST-RP-CC004.2, Sec. 6.1.2
In deionized water; (g/m ²)	0.055	
In isopropanol; (g/m ²)	0.008	
Specific ions		IEST-RP-CC004.2, Sec. 6.2.2
Sodium; (ppm)	1.9	
Chloride; (ppm)	4.7	
Silicone; (ppm)	ND	
Particles, readily releasable		IEST-RP-CC004.2, Sec. 5.1
P ≥ 0.3µm; (x10 ⁶ /m ²)	N/A	
P ≥ 0.5µm; (x10 ⁶ /m ²)	16.5	
Fibers > 100µm; (x10 ³ /m ²)	1.0	IEST-RP-CC004.2, Sec. 5.2
Saturation volume tolerance;		N/A
< 300 mL	+/- 12%	
300 -1666 mL	+/- 3%	
> 1666 mL	+/- 50 mL	

** ND = None detected; levels are below detection limit of test equipment

Part Number	Description	Packaging
SAT-C3-694	6" x 9" (15.2 x 22.9cm) polyester wipe presaturated with 750ml of 6% IPA/94% DI Water, canister with snap-close lid (SAT-CAN120)	100 wipes/roll; 12 rolls/case; 1 canister/case

Notes:

- 1) The information presented here is applicable to the part numbers shown above as well as to any product containing the same materials and produced under the same conditions, regardless of product size or packaging configuration. Please contact a Contec sales representative for more details.
- 2) Data shown are typical values and should not be used as product specifications.
- 3) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- 4) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Revision date: 08/13/08



Copyright © 2008 Contec, Inc. All rights reserved.

North America
P.O. Box 530
Spartanburg, SC 29304 USA
Phone: +1-864-503-8333
www.contecinc.com

Europe
Zl du Prat – RP 3707
56037 VANNES Cedex
FRANCE
+33 297 437 690

China
No.17 Longyun Road
Suzhou 215024
CHINA
+ 86-512-6274 4050