



PINK POLY BAGS

Pink polyethylene antistatic bags with or without zipper.

Film construction :

Antistatic polyethylene

Standard compliance :

IEC 61340-5-1

94/62/EC & 2002/95/EC (RoHS directives)

Material and features :

Material : Pink Polyethylene with antistatic agent
Amine free
Thickness : 50 μ , 75 μ , 90 μ and 150 μ (+/- 5%)
Surface resistance : < 10e11 Ohm
Charge generation : < 50 Volts

Bag specifications :

Dimensions (for non zip bags) : from 76x76mm to 762x914mm
Dimensions (for zipper bags) : from 76x76mm to 406x457mm
All bags dimensions are internal dimensions. The 1st dimension is the opening, the 2nd is the height.
Seal sizes : wire solder
Printing : Standard with ESD requirements, approx 50x50mm,
Blue. Date code (YYMM).
Shelf life : 2 years

Options :

'light version' bags : 50 μ films
(P/N : 20-007-xxxx, 20-008-xxxx, 20-009-xxxx, 20-010-xxxx)

'heavy duty' bags : 90 μ films
(P/N : 20-011-xxxx, 20-012-xxxx, 20-013-xxxx, 20-014-xxxx)

Customized printing on request.



POCHETTES PINK POLY

Pochettes en polyethylene rose antistatique, avec ou sans fermeture à zip

Construction du film :

Antistatic polyethylene

Conformité aux normes :

IEC 61340-5-1

94/62/EC & 2002/95/EC (RoHS directives)

Propriétés matière :

Matière : Polyéthylène rose avec agent antistatique
Sans amines
Epaisseur : 50 μ , 75 μ , 90 μ et 150 μ (+/- 5%)
Résistance de surface : < 10e11 Ohm
Génération de charge : < 50 Volts

Propriétés pochettes :

Dimensions (pochettes sans zip) : de 76x76mm à 762x914mm
Dimensions (pochettes à zip) : de 76x76mm à 406x457mm
Toutes les dimensions sont des dimensions internes. La 1^{ère} dimension indique l'ouverture, la 2^{ème} la hauteur.
Taille de la soudure : soudure par fil
Marquage : Standard avec exigences ESD, environ 50x50mm, Bleu. Date code (YYMM).
Durée de vie : 2 ans

Options :

Pochettes 'light version' : Film 50 μ
(P/N : 20-007-xxxx, 20-008-xxxx, 20-009-xxxx, 20-010-xxxx)

Pochettes 'heavy duty' : Film 90 μ
(P/N : 20-011-xxxx, 20-012-xxxx, 20-013-xxxx, 20-014-xxxx)

Marquage personnalisé sur demande