



# Datasheet

STAXS <sup>®</sup> Reference	Description
D-0046-WSIZE	DOTCH <sup>®</sup> PP/Microporous PE film Coat, PP/microporous PE film, 60g/m <sup>2</sup> , white, size, 1 pc/bag, 25 bags/box



SCIENTIFIC CREDIBILITY

## DOTCH® PP/Microporous PE film Coat

STAXS® Reference : **D-0046-WSIZE**

**DOTCH® PP/Microporous PE film Coat, PP/microporous PE film, 60g/m<sup>2</sup>, white, size, 1 pc/bag, 25 bags/box**



### Features & advantages

- PP/microporous PE film (60g/m<sup>2</sup>)
- Zipper
- Very strong and resistant
- Low level of particle shedding
- Full material traceability
- Verifiable quality from a guaranteed source
- Latex-free elastics
- Recommended for ISO class 7 cleanrooms and higher
- For single use only

Revision date : 18/11/2020

### Physical characteristics

Material	PP/microporous PE film, 60g/m <sup>2</sup>	CE	Cat I (PPER)
Colour	White	Size	S, M, L, XL, 2XL

## DOTCH<sup>®</sup> PP/Microporous PE film Coat

STAXS<sup>®</sup> Reference : **D-0046-WSIZE**

### Technical data

Attribute	Unit	D-0046-WSIZE	Test Methods
Bioburden	CFU	TBC	ISO 11737-1
Particle count	number of particles/cm <sup>2</sup>		Helmke Drum Test IEST-RP-CC003.4
≥0,3-<0,5µm		TBC	Climatic conditions: ISO 6, 18°C ± 2°C, 50% - 10% RH
≥0,5-<1µm		TBC	
≥1-<3µm		TBC	
≥3-<5µm		TBC	
≥5-<10µm		TBC	
≥10µm		TBC	
Shelf life	years	5*	

\* From date of manufacture

### Notes:

- Technical data shown are typical values at the time of publication
- Due to differences in test methods applied and equipment used by different manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility and under similar conditions

Revision date : 18/11/2020



SCIENTIFIC CREDIBILITY

## DOTCH® PP/Microporous PE film Coat

STAXS® Reference : **D-0046-WSIZE**

### Packaging

Product	Ref. No.	Pieces/bag	Bags/box	Box size	Box Weight
DOTCH® PP/Microporous PE film Coat	D-0046-WSIZE	1	25	38x23x26cm	TBC

### Notes:

- Minimum sales unit : 1 box
- Production date, lot number and expiry date can be found on the box
- Box size may vary without affecting the number of pieces in the box or the product itself

### Storage

- Store in dry, clean conditions in the original packaging and keep out of direct sunlight, high temperatures and solvent vapors
- Store between 5°C and 40°C

### Certification

- Produced by STAXS® which is certified ISO 9001:2015

Revision date : 18/11/2020